

# TANDBERG STORAGELOADER 2U LTO

## STORAGELOADER 2U LTO



## Product Highlights

- Maximum capacity of 16 TB\*
- Maximum Transferrate of 576 GB/Hr\*
- Scalable from 10 to 20 Slots
- Slim, 2U rack size
- Bar code reader, rackmount kit, remote management and Symantec Backup Exec QuickStart
- 3 years warranty and 1 year Advanced Replacement Service

\* assume 2:1 data compression

## 20 SLOT 2U LTO AUTOLOADER FOR TRUE ENTRY LEVEL AUTOMATION

The Tandberg StorageLoader 2U LTO easily scales 'on demand' from a 1 x 10 to a 2 x 20 autoloader, with a choice of one or two half-height (HH) LTO-2 drives or a single full-height (FH) LTO-3 drive. It redefines simplicity by offering virtual plug-and-play tape backup and Capacity on Demand by changing drive configuration or adding a second cartridge magazine, all with industry-leading standard features, affordability and warranty support.

### Tape Drive Integration

The Tandberg StorageLoader 2U LTO is configured with one LTO-2 and can be upgraded to hold a second HH drive to double its speed and offer drive redundancy. Adding the second LTO tape drive, field upgrading to next generation LTO drives or to a native FC interface can be completed while the library is still in its rack. Upgrading from an LTO-2 drive to an LTO-3 SCSI or native Fibre-Channel drive doubles capacity and more than triples the LTO-2 drive speed.

### Media Compatibility

The Tandberg StorageLoader 2U LTO is compatible with Ultrium™ data cartridges. The StorageLoader 2U LTO can accommodate up to 20 cartridges.

### Upgrade Magazine

The StorageLoader 2U LTO ships with a right hand (RH) magazine that includes an I/E port. Adding the second LH magazine the StorageLoader 2U LTO inexpensively doubles the storage capacity of the original library.

### Five reasons to select the Tandberg StorageLoader 2U LTO

- **Choice**  
Supports up to two LVD SCSI LTO-2, one LVD SCSI LTO-3 drive or one native FibreChannel LTO-3 drive in only 2U rack space.
- **Capacity and Performance**  
Delivers up to 4 to 16 TB\* of capacity at a transfer rate of up to 173 GB/Hr to 576 GB/Hr\*.
- **Upgrade Path**  
Easily and inexpensively double your speed by upgrading to a second HH drive, even when installed in a rack. By upgrading to a FH LTO-3 capacity can be doubled with the potential to more than triple your speed.
- **User friendly**  
Uses an intuitive, user-friendly LCD interface to guide you through configuration, status, diagnostics and help functions.
- **Scalable**  
Easily scales from 10 to 20 slots by simply adding a magazine.

## STORAGELOADER 2U LTO



### About Tandberg Data

Tandberg Data is a leading global supplier and manufacturer of tape drives, tape automation and disk sub-systems. Tandberg Data offers solutions based on the LTO™, SLR™ and VXA™ tape technology platforms, storage software, media and disk-based storage. All solutions are designed to meet the growing storage requirements of small and medium-sized organisations with scalability, reliability and backward compatibility features that ensure cost effective operation and long-term investment protection. Tandberg Data has been proudly servicing its customers for over 25 years, and customer service is fundamentally important to Tandberg Data.

## Specifications

Tape Drive	LTO-2 HH SCSI	LTO-3 FH SCSI	LTO-3 FH FC
Drive Technology:	1 (expands to 2 drives)	1	1
Capacity native (10 Slots):	2 TB	4 TB	4 TB
Capacity native (20 Slots):	4 TB	8 TB	8 TB
Capacity compr. (10 Slots)*:	4 TB	8 TB	8 TB
Capacity compr. (20 Slots)*:	8 TB	16 TB	16 TB
Transfer rate (native):	86 GB/Hr	288 GB/Hr	288 GB/Hr
Transfer rate (compr.):*	346 GB/Hr	576 GB/Hr	576 GB/Hr
Interface:	LVD SCSI	LVD SCSI	Native FC
Barcode Reader:	Yes	Yes	Yes
Rackmount Kit:	Standard 19" Rack kit	Standard 19" Rack kit	Standard 19" Rack kit
<b>Dimensions</b>			
Form Factor:	2U		
Length:	77.54 cm		
Width:	44.63 cm		
Depth:	8.75 cm		
Weight:	19.5 kg		
<b>Power requirements</b>			
Voltage:	100 – 240 V AC, 50 to 60 Hz		
Library (maximum operating):	65 Watts RMS		
<b>Environmental Specification</b>			
Temperature (operating):	10° C to 40° C		
Temperature (non-operating):	-40° C to 65° C		
Relative Humidity (operating, non-condensing):	20 % to 80 %		
Relative humidity (non-operating, non-condensing):	10 % to 90 %		
<b>Certification</b>			
Agency Certifications:	CE, UL, C-UL, FCC-A, VCCI, C-Tick, GS, IEC-60950-1, WEEE, ROHS		
<b>Reliability</b>			
MTBF:	> 250.000 hours		
MTTR (Mean Time To Repair):	< 20 minutes		
<b>Connectivity</b>			
	SCSI LVD, 68-pin HD	DB Multimode FC, Single optical LC port	DB Multimode FC, Single optical LC port
<b>Warranty</b>			
	3 years warranty and 1 year Advanced Replacement Service		

\* assume 2:1 data compression

### Model numbers

StorageLoader 2U LTO, 1 x 10 FH LTO-3 FC	052152
StorageLoader 2U LTO, 1 x 20 FH LTO-3 FC	052153
StorageLoader 2U LTO, 1 x 10 HH LTO-2	052202
StorageLoader 2U LTO, 1 x 20 HH LTO-2	052203

Additional configurations available.  
Please contact Tandberg Data for further information.

### Media

Tandberg LTO-1 Data Cartridge	0043 2630-1
Tandberg LTO-2 Data Cartridge	0043 2744
Tandberg LTO-3 Data Cartridge	0043 3216
Tandberg LTO Cleaning Cartridge	0043 2631

Tandberg Data ASA  
Kjelsåsveien 161  
0411 Oslo  
Norway

T +47 (0) 2218 9090  
F +47 (0) 2218 9550

Tandberg Data UK Ltd.  
Bloxham Mill Business Park  
Barford Road  
Bloxham – Banbury  
Oxfordshire  
OX15 4FF  
United Kingdom

T +44 (0) 8450 706 916  
F +44 (0) 1295 722 801

Tandberg Data GmbH  
Feldstrasse 81  
44141 Dortmund  
Germany

T +49 (0) 231 5436 - 0  
F +49 (0) 231 5436 - 111

Tandberg Data S.A.  
16-18, avenue Morane  
Saulnier – BâtA  
78941 Vélizy Cedex  
France

T +33 (0) 139 260 101  
F +33 (0) 134 650 289

Tandberg Data Corp.  
2108 55th Street  
Boulder, CO 80301  
USA

Toll Free +1 800 392 2983  
Local (303) 442 4333

Tandberg Data (Japan) Inc.  
Eitaibashi Eco-Piazza Bldg.  
8th floor  
29-13, Shinkawa 1-chome,  
Chuo-ku  
Tokyo 104-033  
Japan

T +81 (0) 355 662 871  
F +81 (0) 355 662 875

Tandberg Data (Asia)  
Pte-Ltd  
20 Bendemeer Road  
#04-05 Cyberhub  
Singapore 339914

T +65 (0) 6396 0786  
F +65 (0) 6396 0787

Specifications subject to change without notice. All product and company names are trademarks or registered trademarks of their respective companies. © 2007 TANDBERG DATA. All rights reserved. DS-2007-ENG-03-0005